RTX-BASED CORRECTION SERVICES NEW!

Some crops can be grown most profitably using sub-inch accuracy corrections. Others don't require such precision. Trimble's RTX-based correction services provide GNSS-enabled, high-performance correction options ranging from high-accuracy to entry-level in a variety of delivery options. And with availability throughout the world, you can benefit from unmatched reliability and uptime no matter where you are located.

- » The accuracy you need Choose the right accuracy for your farming applications. RTX technology enables high-accuracy CenterPoint[™] RTX corrections as well as entry-level, broad-accuracy RangePoint[™] RTX corrections.
- » Increased satellite availability RTX technology is GNSS compatible, allowing you to use GPS and GLONASS satellite signals on your existing FmX[®] integrated display, CFX-750[™] display, and AG-372 GNSS receiver.
- » Free GLONASS With an active CenterPoint RTX or RangePoint RTX subscription, GLONASS satellite access is unlocked for free throughout the duration of the subscription. Using GLONASS in addition to GPS can improve signal reception, reduce blockage, and result in higher quality positioning.
- » More uptime Continue working during times of correction signal loss for up to two minutes.
- » Fast initialization Full accuracy can be achieved in 30 mins or less using the CenterPoint RTX[®] correction service and 5 mins or less using the RangePoint RTX correction service.
- » No base station needed No need to fear losing radio signal reception since a base station is not needed for RTX-based correction services.
- » Available everywhere The CenterPoint RTX correction service is available throughout the entire world via mobile data network. CenterPoint RTX and RangePoint RTX corrections are available throughout most of the world via satellite delivery.



CENTERPOINT RTX CORRECTION SERVICE



RANGEPOINT RTX CORRECTION SERVICE

Satellite Availability Only

Trimble Agriculture Correction Services

No matter where you're located. No matter what you farm. Trimble has a correction services solution to meet your needs.

SUB 4 CM ACCURACY	SUB 10 CM ACCURACY
CenterPoint RTK	OmniSTAR HP
CenterPoint VRS	OmniSTAR XP
CenterPoint RTX	OmniSTAR G2

For more information on any of Trimble's correction services, visit www.trimble.com/agcorrectionservices or contact your local Trimble reseller.

NORTH & SOUTH AMERICA

Trimble Agriculture Division 10355 Westmoor Drive, Suite #100 Westminster. CO 80021 +1-720-887-6100 Phone +1-720-887-6101 Fax

Trimble Navigation Limited Corporate Headquarters 935 Stewart Drive Sunnyvale, CA 94085 +1-408-481-8000 Phone +1-408-481-7740 Fax

© 2011-2013, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and FmX are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. CenterPoint, CFX-750, Connected Farm, OmniSTAR, RangePoint, RTX, VRS, and xFill are trademarks of Trimble Navigation Limited. All other trademarks are the property of their respective owners. PN 022503-864E (01/13)

www.trimble.com/agcorrectionservices

SUB METER ACCURACY

RangePoint RTX **OmniSTAR VBS**

Trimble Germany GmbH

+49-6142-2100-226 Phone

+49-6142-2100-140 Fax

Am Prime Parc 11

65479 Raunheim

GERMANY

EUROPE

ASIA-PACIFIC

Trimble Navigation Australia PTY Limited Level 1/120 Wickham Street Fortitude Valley, QLD 4006 AUSTRALIA +61-7-3216-0044 Phone +61-7-3216-0088 Fax



Trimble.

AGRICULTURE **CORRECTION SERVICES**



OUR GOAL:

TO PROVIDE FARMERS AROUND THE WORLD WITH THE ACCURACY THEY NEED.

No matter where you're located. No matter what you farm. Trimble has a correction services solution to meet your needs.

Trimble delivers precision agriculture solutions for all seasons, all crops, all terrains and all vehicles. Knowing that every farmer's accuracy requirements are different, Trimble offers a wide range of correction services.

PLEASE KEEP THE FOLLOWING OUESTIONS **IN MIND AS YOU EXAMINE THE OPTIONS AVAILABLE TO YOU:**

- » What level of accuracy does your farming application require?
- » Where are you located?
- » Do you have a reliable RTK base station network in your area? (See Dealer Locator at www.trimble.com/locator)
- » Do you have reliable cellular coverage in your area?



Trimble's DCM-300 Modem

Trimble's DCM-300 modem is an all-in-one modem for use with CenterPoint VRS[™], or CenterPoint RTX corrections delivered over mobile data network. In addition to providing RTK-level corrections, the DCM-300 modem can also be used to perform wireless activities with Trimble's Connected Farm[™]. This dual purpose capability streamlines your hardware needs and lowers your start-up costs.

SUB 4 CM ACCURACY

CenterPoint RTK

ACCURACY < 1" (2.5 cm)

CenterPoint RTK is best suited for:

- Farms within 8 miles of an established RTK base station or base station network
- Farms without line-of-sight obstructions such as hilly terrain or an abundance of trees
- Use with applications in which the best horizontal and vertical accuracy is required
- NEW! Receive supplemental xFill[™] signals when an RTK signal is lost—helping you increase your uptime and maximize productivity until your RTK signal is restored.

CenterPoint VRS

ACCURACY

< 1" (2.5 cm)

CenterPoint VRS is best suited for:

- Farms in areas with robust cellular coverage
- Operations spread out over a large geographic area
- Use with row crops, strip tilling, and other applications requiring sub-inch (sub 2.5 cm) accuracy

CenterPoint RTX

ACCURACY 1.5" (3.8 cm)*

CenterPoint RTX is best suited for:

- Farms located anywhere in the world
- Farms outside of RTK base station coverage areas
- Use with the Trimble FmX integrated display, CFX-750 display, or AG-372 GNSS receiver
- Use with row crops and other applications requiring 1.5" (3.8 cm)** accuracy

* Receiver convergence time varies based on GNSS constellation health, level of multipath, and proximity to obstructions such as large trees and buildings. In ideal conditions, receivers can converge to a 30 cm position in approximately 10 minutes, 20 cm in 15 minutes, and full accuracy in less than 30 minutes.

** All horizontal accuracy specifications are based on repeatable in-field performance 95% of the time.

SUB 10 CM ACCURACY

SUB METER ACCURACY

INITIALIZATION/CONVERGENCE < 1 min



INITIALIZATION/CONVERGENCE < 1 min



INITIALIZATION/CONVERGENCE < 1 min Standard*

Contact your local Trimble Reseller to determine if your area has RTK base station coverage.

To find a reseller near you visit, www.trimble.com/locator.

OmniSTAR HP

ACCURACY

2-4" (5–10 cm)

OmniSTAR[™] HP is best suited for:

- High-performance broadacre seeding, spraying and harvesting applications
- Operations in areas with open views of the sky at all times

OmniSTAR XP

OmniSTAR XP is best suited for:

land-tillage applications

sky at all times

• High-performance broadacre spraying and

• Operations in areas with open views of the

ACCURACY 3-4" (8–10 cm)

INITIALIZATION/CONVERGENCE

INITIALIZATION/CONVERGENCE

Standard*



OmniSTAR G2

ACCURACY

INITIALIZATION/CONVERGENCE

3-4" (8–10 cm)

OmniSTAR G2 is best suited for:

- Use when more reliable coverage time is necessary, due to the use of GLONASS satellites in addition to the standard GPS satellites
- Operations in areas with open views of the sky at all times





RangePoint RTX is best suited for: correction service

- areas where SBAS is not available

available for any compatible product.***



OmniSTAR VBS


CCURACY	INITIALIZATION/CONVE
< 1 meter	<

- repeatability
- Broadacre crop spraying, tillage applications, and other applications in



***Valid in 2013. Other restrictions may apply.

MOBILE DATA AVAILABILITY



SATELLITE AVAILABILITY





Standard*

1/16/2013 2:25:26 PM